



KOBH

Altezza Seat-tube height H	CF	Lunghezza Top-tube length L c/c	Inclinazione Seat-tube angle		Punte forcella scatola Fork to bottom bracket S	Scatola/ forcellino posteriore Chain stay to bottom bracket center AR	Altezza terra Bottom bracket height F	Curva forcella Fork rake F	Angolo Sterzo Steering Angle Y	Misura Sterzo Steering Sizes A
			α	$\alpha1$						
			gradi/degrees	mm						
420	450	500	73,40°	120	561	413	270	47	69,50°	110
450	480	520	73,40°	128.5	571	413	270	47	71,00°	120
485	515	540	73,00°	142	573	413	265	47	73,00°	135
510	540	555	73,00°	149	588	413	265	47	73,00°	150
520	550	560	73,00°	152	592.5	413	265	47	73,00°	155
530	560	570	73,00°	155	602	413	265	47	73,00°	165
540	570	580	73,00°	158	612	413	265	47	73,00°	180
550	580	585	72,50°	165	612	413	265	47	73,00°	200

DOGMA® • PARIS • FPQUATTRO • FP3

Altezza Seat-tube height H	CF	Lunghezza Top-tube length L c/c	Inclinazione Seat-tube angle		Punte forcella scatola Fork to bottom bracket S	Scatola/ forcellino posteriore Chain stay to bottom bracket center AR	Altezza terra Bottom bracket height T	Curva forcella Fork rake F	Angolo Sterzo Steering Angle Y	Misura Sterzo Steering Sizes A
			α	$\alpha1$						
			gradi/degrees	mm						
420-Only	440	498	74,40°	113	563	406	270	43	69,15°	110
440s	460	503	74,40°	118	565	406	270	43	70,00°	115
465s	485	515	74,40°	124	575	406	270	43	70,50°	120
500	520	525	74,00°	138	575	406	265	43	71,40°	125
515	535	535	73,70°	145	577,5	406	265	43	72,00°	130
530	550	545	73,70°	149	583	406	265	43	72,50°	144
540	560	550	73,40°	154	583	406	265	43	72,80°	152
550	570	557	73,40°	157	590	408	265	43	72,80°	163
560	590	565	73,00°	163	592	408	265	43	73,20°	170
575	595	575	73,00°	168	596	408	265	43	73,70°	184
595	615	587	72,40°	180	605	408	270	43	73,40°	210
620-Only	640	620	72,00°	192	633	411	270	43	73,40°	240

PARIS • FPQUATTRO • FP3 EASYFIT

425	445	500	74,00°	117	565	406	265	43	70,00°	120
460	480	512	74,00°	127	570	406	265	43	71,00°	135
490	510	528	73,50°	139	575	406	265	43	72,00°	145
510	530	545	73,00°	149	588	406	265	43	72,00°	155

FP2

440	460	505	74,40°	118	565	406	270	43	70,20°	120
470	490	528	74,00°	129,5	579	406	265	43	71,00°	125
510	530	537	73,50°	145	580	406	265	43	71,70°	131
530	550	550	73,50°	152	583	406	265	43	72,70°	153
550	570	560	73,00°	161	589	408	265	43	72,80°	168
570	590	575	72,50°	171	598	410	270	43	73,00°	185
590	610	585	72,00°	182	597	410	270	43	73,00°	208

